


# CURVY



STANDARD: LEDpanel



OPTIONAL:  
LED-Globe E27 Socket



## TECHNICAL SPECIFICATIONS CURVY



IP20

AC

230V



120 °



Input Voltage: AC85-265V, 50/60Hz

LED Power CURVY60: 24W (2160lm)

LED Power CURVY75: 24W (2160lm)

LED Power CURVY90: 28W (2520lm)

Efficiency(lm/w): 90lm/w

LED Type: SMD2835 (LEDpanel)

Color Rendering Index(CRI): 80 Ra

Dimensions CURVY60: Ø60x30cm

Dimensions CURVY75: Ø75x37cm

Dimensions CURVY90: Ø90x45cm

Cable length: 200cm

Control: LampSmartPro app/Remote




3000K

CCT-DIM

6000K



3000K



4000K



6000K




Ø60



Ø75



Ø90



Ø120

## TECHNICAL SPECIFICATIONS PETBOARD

Composition: 100% PET (> 70% recycled PET)

Thickness: 9mm

Density: 210kg/m3

Weight: 1900g/m2 (± 2%)

Number of PET-bottles: 55/m2

PETpanel colors: 33

Fire test EN 13501-1: B-S1, d0

Sound absorption petboard aw/m2: 0,25

Sound absorption petboard NRC/m2: 0,30



DESIGNS TRACKER

© 2025 Designstracker. All rights reserved



DESIGNS TRACKER

© 2025 Designstracker. All rights reserved